DIMENSIONS

Unit: mm							ı +
8						**************************************	9
				6	7		†
· L							
1-	·						
Range (n	nm)	ød	1	L	øD	l	
3 - 5		2.8 -	5.2	90	5.5	22.5	
5 - 7.5	5	4.8 - 7.8		97.6	5.5	30	
7.5 - 1	0	7.3 - 10.3		108	8.5	40	
10 - 1	3	9.8 - 13.2		100	0.5	40	

Small Hole Gage Set SERIES 154

- Extra long for gaging deep and shallow holes, slots, and similar workpiece features.
- Two sprung leaves are fully expanded inside a feature so that its size can be measured with an outside micrometer after extraction.




SPECIFICATIONS

Metric				
Order No.	Range (mm)			
4-gage Set				
154-902	3 - 13			
Gages included				
154-101	3 - 5			
154-102	5 - 7.5			
154-103	7.5 - 10			
154-104	10 - 13			

Inch			
Order No.	Range (in)		
4-gage Set			
154-901	0.125 - 0.5		
Gages included			
154-105	0.125 - 0.2		
154-106	0.2 - 0.3		
154-107	0.3 - 0.4		
154-108	0.4 - 0.5		

DIMENSIONS



Telescoping Gage Set SERIES 155

• A spring-loaded plunger expands within a bore (or groove) and is locked in place allowing measurement of diameter (or width) with an outside micrometer after extraction.



SPECIFICATIONS

Order No. Range (mm) 6-gage Set 155-905 8 - 150 Gages included 155-127 8 - 12.7 155-128 12.7 - 19 155-129 19 - 32 155-130 32 - 54 155-131 54 - 90 155-132 90 - 150	Metric	
155-905 8 - 150 Gages included 155-127 8 - 12.7 155-128 12.7 - 19 155-129 19 - 32 155-130 32 - 54 155-131 54 - 90	Order No.	Range (mm)
Gages included 155-127 8 - 12.7 155-128 12.7 - 19 155-129 19 - 32 155-130 32 - 54 155-131 54 - 90	6-gage Set	
155-127 8 - 12.7 155-128 12.7 - 19 155-129 19 - 32 155-130 32 - 54 155-131 54 - 90	155-905	8 - 150
155-128 12.7 - 19 155-129 19 - 32 155-130 32 - 54 155-131 54 - 90	Gages included	
155-129 19 - 32 155-130 32 - 54 155-131 54 - 90	155-127	8 - 12.7
155-130 32 - 54 155-131 54 - 90	155-128	12.7 - 19
155-131 54 - 90	155-129	19 - 32
	155-130	32 - 54
155-132 90 - 150	155-131	54 - 90
	155-132	90 - 150

Inch	ı
Order No.	Range (in)
6-gage Set	
155-903	0.313 - 6
Gages included	
155-121	0.313 - 0.5
155-122	0.5 - 0.75
155-123	0.75 - 1.25
155-124	1.25 - 2.125
155-125	2.125 - 3.5
155-126	3.5 - 6

