Vernier Height Gage SERIES 514, 506 — Standard Height Gage with Adjustable Main Scale

- Fits comfortably in the hand and moves easily on the surface plate.
- The main scale slides and clamps within the column for quick and convenient zero-setting.
- Large locking knobs are used both for the slider and fine adjustment clamps to make clamping easy and secure.
- Operability of slider has been improved.







- Large main-scale engraving for fatigue-free working.
- Carbide-tipped scriber (07GZA000 for 514-102/ 104/106/103/105/107,


905200 for **514-108** and **109**) is provided as a standard accessory. (Scriber clamp 05GZA033 for 514-102/104/106/108/103/105/107/109)

21

20

19

- It is important for personal safety to ensure that any height gauge remains stable in use after attaching an accessory such as a test indicator or
- For precision Black Granite Surface Plates, refer to page E-49.



506-207

SPECII

FICATIONS	514-102

Wettle								
Order No.	Range (mm)	Minimum reading (mm)	Scale adjustmen (mm)	Fine feed (mm)	Maximum Permissible Error* (mm)/Enpe	Height (mm)	Mass (kg)	Remarks
506-207	0 - 200	0.02	_	4	±0.03	341	1.4	_
514-102	0 - 300		15		±0.04	525	3.1	_
514-104	0 - 450				±0.05	675	3.4	_
514-106	0 - 600			7		870	7.4	_
514-108	0 - 1000		25	6	±0.07	1340	20	_

* Maximum Permissible Error, EMPE, is the term (notation) used in JIS B 7517: 2018, revised based on ISO/TR 14253-6: 2012.

Inch/Metric

Order No.	Range (in)	Minimum reading	Scale adjustmen (in)	Fine feed (in)	Maximum Permissible Error* (in)/ENPE	Height (mm)	Mass (kg)	Remarks
506-208	0 - 8	0.001 in/0.02 mm	_	0.16	±0.001	341	1.4	_
514-103	0 - 12		0.6		±0.002	525	3.1	_
514-105	0 - 18					675	3.4	_
514-107	0 - 24			0.27		870	7.4	_
514-109	0 - 40		1	0.24	±0.003	1340	20	_

* Maximum Permissible Error, EMPE, is the term (notation) used in JIS B 7517: 2018, revised based on ISO/TR 14253-6: 2012.

DIMENSIONS

